

LANIER

SP 3400N/SP 3410DN



B/W LASER PRINTER

Business printing in a desktop solution

Cost-effective networked laser printing that is right at home in large and small offices.



LANIER**SP 3400N/SP 3410DN****Designed for Your Desktop and Budget**

Choose from two compact models designed to meet today's space, workflow and purchasing requirements while investing in a solution that will serve tomorrow's needs as your business grows. The LANIER® SP 3400N/SP 3410DN bring productive black & white network laser printing to home offices and small businesses at a low total cost of ownership.

Maximum Productivity, Minimal Effort

Fast, reliable and easy to use, the Lanier SP 3400N Series brings professional printing capabilities to every user.

- Finish every job faster with efficient 30-ppm output speeds, and make every page look its best with laser-sharp 1200 x 600 dpi maximum resolution.
- Process every file with ease. The 295MHz CPU and standard 64 MB RAM quickly handle incoming data streams in popular PCL 6 or PostScript 3 emulation to keep the pages flowing.
- Leverage the power of standard Ethernet networking to allow every employee to share the printer. A USB 2.0 interface is also standard to drive the unit through a single Windows PC or Mac.
- Save time and energy with a fast 20-second warm-up time and first print speeds of just 8 seconds.

Versatile, Expandable Media Support

The Lanier SP 3400N Series supports demanding workloads with a variety of media requirements.

- Choose the Lanier SP 3410DN with standard automatic duplexing for productive two-sided printing, or the more economical Lanier SP 3400N for offices with single-sided output needs.
- Print onto a wide range of media sizes up to 8.5" x 14" and paper weights up to 90 lb. Index. User-adjustable, front-loading paper trays enhance system flexibility.
- Speed envelope printing via the 50-Sheet Bypass Tray for in-house customer invoicing and mailing applications.
- Expand paper capacity up to 550 sheets to handle longer jobs and growing volumes with less interruption. The optional 250-Sheet Paper Feed Unit installs beneath the standard 250-Sheet Tray to maintain a compact footprint.

Affordable and Virtually Maintenance Free

Compact and cost-effective, the Lanier SP 3400N Series maximizes productivity while helping to control printing costs.

- Invest with confidence. Aggressive hardware pricing, a robust feature set and a high duty cycle deliver superior value and a low total cost of ownership.
- Choose the Standard Yield All-In-One (AIO) print cartridge (2,500 pages) to minimize out-of-pocket supply expenses, or the High Yield AIO (5,000 pages) to bring cost-per-page factors down even more.
- Simplify consumable replacement. Exchange the front-loading AIO print cartridge in seconds in a quick, mess-free process.
- Use integrated Automatic Duplexing (Lanier SP 3410DN) to save paper, mailing costs and filing space.

SPECIFICATIONS

Configuration Technology	Desktop Laser beam scanning, electrophotographic printing using dry mono-component toner development
Resolution	600 x 600 dpi, 1200 x 600 dpi equivalent
Print Speed	30 pages-per-minute (Letter)
First Print Speed	8 seconds or less
Warm-Up Time	20 seconds or less
Maximum Paper Size	8.5" x 14"
Standard Paper Supply	250-Sheet* Tray + 50-Sheet* Bypass Tray
Optional Paper Supply	250-Sheet* Paper Feed Unit
Maximum Paper Capacity	550 sheets
Output Capacity	125 sheets (face down)
Duplexing	Manual: SP 3400N Automatic: SP 3410DN (approx. 50% productivity)
Paper Sizes	Paper Tray: 8.5" x 11" to 8.5" x 14"; A4, B5, A5, A6, HLT, Executive, Foolscap, Folio; Custom Size: 3.94" x 5.83" to 8.5" x 14.02" Bypass Tray: 8.5" x 11" to 8.5" x 14"; A4, B5, A5, A6, HLT, Executive, Foolscap, Folio; Custom Size: 3.54" x 5.92" to 8.5" x 14.02" Optional Paper Feed Unit: 8.5" x 11" to 8.5" x 14"; A4, B5, A5, HLT
Paper Weights	Standard & Bypass Tray: 14 - 43 lb. Bond/90 lb. Index (52 - 162 g/m ²) Optional Paper Feed Unit: 16 - 28 lb. Bond (60 - 105 g/m ²) When Duplexing: 16 - 28 lb. Bond (60 - 105 g/m ²)
Paper Types	Standard Tray: Plain Paper, Recycled Paper Bypass Tray: Plain Paper, Recycled Paper, Envelopes, Labels Optional Paper Feed Unit: Plain Paper, Recycled Paper
Dimensions (WxDxH) Weight	14.5" x 15.4" x 10.3" (370 x 392 x 262 mm) SP 3400N: 25.6 lb. (11.6 kg) (includes AIO) SP 3410DN: 27.6 lb. (12.5 kg) (includes AIO)
Power Requirements Power Consumption	120V, 60Hz Maximum: 850W, Energy Saver: 5W Energy Star v. 1.1 compliant
Safety Regulations	UL60950-1, FCC Class B
	*Using 20 lb. Bond Paper

PRINT CONTROLLER SPECIFICATIONS

CPU	295MHz
Memory	64 MB RAM standard/maximum
Standard Interfaces	USB 2.0, Ethernet 10/100Base-TX
Printer Languages/Drivers¹	PCL 6, PostScript 3 emulation
Fonts	PCL/PS 3: 80 fonts
Network Protocols	TCP/IP, IPP
Operating Systems	Windows 2000, XP, Server 2003/2008R ² , Vista, 7 ² Macintosh OS X v.10.2.8 - 10.6 ² Citrix Presentation Server Lanier UNIX Filter ³
Advanced Printer Features	Scaling, Collate, Layout/N-Up, Front Cover Sheet, Dithering, Watermarks, Rotate Print, Toner Saving, Mirror Image (PS3), Reverse Order Print (PS3), Do Not Print Blank Pages (PS3)
Software Utilities	Web Image Monitor (when connected to a LAN) Printer Utility for Mac @Remote (limited support)

¹PCL 5e does not ship with the product, but the controller can receive PCL 5e information from the host computer.

²Available via download from the Lanier website.

³Please check www.lanier.com for final release date.

OPTIONAL ACCESSORIES

250-Sheet Paper Feed Unit TK1080
Lanier BB-HPL10A-R High Definition Power Line Communications Ethernet Adaptor
USB Cable (A - B) 6'

SUPPLIES

Consumable	Yield
Standard Yield All-In-One Cartridge	2,500 pages ⁴
High Yield All-In-One Cartridge	5,000 pages ⁴

⁴Declared yield values based on ISO/IEC 19752.

Actual yields may vary based on types of images printed and other factors.

The Lanier SP 3400N/SP 3410DN ships with a starter All-In-One print cartridge yielding 1,500 pages. All other consumables ship at full yield.

For maximum performance and yield, we recommend using genuine Lanier parts and supplies.

WARRANTY

The Lanier SP 3400N/SP 3410DN is under warranty against defects for a period of one year from the date of purchase. Consumables are under warranty for a period of 90 days from the date of purchase. Please refer to warranty documents shipped with the product for more details.

www.lanier.com

Bringing Lanier Value to Your Organization
Lanier technology offers a diverse portfolio of solutions to help your organization stay competitive and move ahead. Let Lanier show you how to empower your business to improve critical processes, keep information secure, ensure compliance and promote environmental sustainability while reducing the total cost of ownership.

Lanier Five Dedrick Place, West Caldwell, NJ 07006
©2010 Lanier is a registered trademark of Ricoh Americas Corporation. All rights reserved. All other trademarks are the property of their respective owners. Print speed may be affected by network, application or PC performance. Specifications and external appearances are subject to change without notice. Products are shown with optional features.

L3165

